# **SPECIFICATION SHEET**

# LED SMD YELLOW Floodlight

The LED SMD Floodlight has a yellow finish and is suitable for 110V site lighting applications.

## Applications

Site Lighting 
Commercial Sites 
Factories 
Retail



# Specification

| LED:                       | 100pcs of SMD 5730 |
|----------------------------|--------------------|
| Material:                  | Aluminium          |
| Lumen Output:              | 4000lm             |
| <b>Colour Temperature:</b> | 6500K              |
| Guarantee:                 | 3 Years            |
| Life Expectancy:           | 35,000 Hours       |
| Working Temperature:       | : -20°C - 40°C     |
| Power Factor:              | >0.9               |
| Beam Angle:                | 120°               |
| CRI:                       | >70Ra              |

## **Additional Information**


RED: ARROW

- 1m H05VV-F 3G1.0 Cable included.
- Powder coated finish in Yellow



2

## Dimensions



| Code       | Wattage                           | Lumen Output | Dimensions (L x W x D mm) |
|------------|-----------------------------------|--------------|---------------------------|
| FLSMD50Y-1 | 50W                               | 4000lm       | 310 x 315 x 65            |
|            |                                   |              |                           |
|            | T: 0800 195 0006 F: 0870 195 0006 |              | Red Arrow Trading         |

E: sales@redarrowtrading.com

www.redarrowtrading.com

Elsworth House, Herries Road South Sheffield, S6 1QS